



IP Networking Camera: SONE-CCD2000 MPEG4 Pan / Tilt / 10X Optical Zoom



Key features:

- MPEG4/ MJPEG Compression selectable
- Motorized Pan/Tilt/Zoom (10x optical zoom)
- Optimal Synchronization of Audio & Video
- Supports Auto Pan/ Auto Patrol modes
- Supports UPnP & DDNS
- Intelligent Motion Detection
- Supports Pre/Post Alarm Snapshots
- Extended I/O for Sensor & Alarm
- Built-in Two-way Audio
- Bundles 16-channel monitoring software



Internet Camera



Features

- Motorized Pan and Tilt via Web remote control
- CCD Sensor for superior quality image
- Pan: Range 270 degree, Tilt: Range 135 degree
- IEEE 802.11g Wireless LAN standard with 64/128-bit WEP keys
- Fast Ethernet 10/100 Mbps Connectivity
- 10X Optical Zoom
- 10X Digital Zoom
- High quality MPEG4 short header mode compression
- Built-in omni-directional microphone
- Remarkable motion detection & Email alerts
- AV output to external monitor
- Easy setup and Installation (UPnP supported)
- 16-channel monitoring software

Package Contents:

- Wired or wireless Internet Camera
- Power Adaptor
- Camera Stand
- Software CD-ROM
- Quick Installation Guide
- A/V Cable
- Antennas for wireless system only
- Remote Controller

System Requirements:

- Internet Explorer 6.x or Above
- Computer with Pentium III, 800MHz and 128MB Memory Running Microsoft Windows XP/2000/Me/98SE for Remote Management Software
- VGA card resolution : 800 x 600 or Above








สนใจ สอบถามรายละเอียดเพิ่มเติม กรุณาติดต่อ
 บริษัท เอส-วัน เทคโนโลยี จำกัด โทร. 02-991-6962 มือถือ 06-789-7434
 Email: kitti@sone.co.th



7-inch Wall-mounted Dome Camera outdoor For Pan/Tilt/ZOOM Camera

7-inch Wall-mounted Dome Camera with Inner Aluminum PT - JP1707WA

New Features

- Preset Function(Max 60 Presets)
- Tour Function
- Auto Scan
- Small Volume and few wastage
- Simple installation

Features

- Double-deck shell design, Air convection, More acclimatization
- Separate Design for mechanism and dome.
- The mechanism can be removed sily.
- It is convenient for installation ebugging and maintenance.
- Separate packages of mechanism, dome, and housing. Avoid damage from the transit.
- Pan/Tilt limit angle is adjustable.
- Outdoor models: With inner auto thermostat
- Connect part between dome and mechanism is processed specially. It cannot disconnect or be oxidized forever.

Key Specifications/Special Features:

Designed for outdoor use, fast installation

Input voltage: 24V AC, 50/60Hz

Power: 21W

Construction:

Top housing: ABS fireproof material

Inner PT: aluminum

Dome cover: PMMA

Color:

Top housing: white

Dome cover: light blue

Turn angle:

Pan: 0 to 356 degrees

Tilt: 0 to 90 degrees

Speed:

Pan: 10 degrees/s



Tilt: 10 degrees/s
Pan/tilt adjustable
Working temperature: -30 to 60 degrees Celsius
Inner heater
On: 0 degrees Celsius
Off: 10 degrees Celsius
Inner fan
On: 40 degrees Celsius
Off: 30 degrees Celsius
Mount: wall mount
Dimensions: 239 x 344mm

Sample Viewer mode 320

PSD demo(HTTP-V) 2006/03/20 16:29:39

Run GP:02 P001

Snapshot

Client setting

Up

Left Home Right

Down

- Zoom +

- Auto Focus +

Pan speed 1

Tilt speed 0

Zoom speed -1

Go to -- Select one --

PSD demo(HTTP-V) 2006/03/20 16:31:37

Run GP:02 P003

Snapshot

Client setting

Up

Left Home Right

Down

- Zoom +

- Auto Focus +

Pan speed 1

Tilt speed 0

Zoom speed -1

Go to -- Select one --