



## กล้อง IP Camera รุ่น PP-201IR Plug and Play IR CCD



### Features:

- **Plug & Play**

PP-201IR is a plug & play IP camera that makes network set-up easy. Once installed, set-up is as simple as entering ID and password using GKB ZIP View™ software.

- **3G Mobile Access**

PP-201IR enables 3G mobile surveillance by RTSP. With mobile version NVR, surveillance is done by simply entering ID and password, on most mobile phones of Windows Mobile, Symbian, and iPhone OS.

- **Built-in Infrared**

Infrared sensors inside the camera's housing provide the ability to capture images during night and low-light conditions.

- **MPEG4 Video Compression**

PP-201IR features MPEG4 video compression for superior video quality. Image quality is enhanced by avoiding the conversion of analog signals to digital before transmission.

- **Weatherproof Housing**

Weatherproof housing allows PP-201IR to be installed in most applications and environments, including in summer, winter, sunny day or rainy day; making it an ideal camera for outdoor surveillance.

สนใจ สอบถามรายละเอียดเพิ่มเติม กรุณาติดต่อ  
บริษัท เอส-วัน เทคโนโลยี จำกัด โทร. 02-991-6962 มีมือถือ 086-789-7434  
Email: [kitti@sone.co.th](mailto:kitti@sone.co.th)  
[www.sone.co.th](http://www.sone.co.th)



Specification:

Video	Image Sensor	1/3" Sony CCD
	Number of Effective Pixels	NTSC: 510(H) * 492 (V) PAL: 500(H) * 582 (V)
	Video Compression	MPEG 4
	Video Streams	2
	Resolution	176 * 120, 352 * 240, 720 * 480
	Frame Rate	Up to 30 FPS in All Resolution
	Min. Illumination	0.5 Lux, 50 IRE, F1.4
	Gamma	0.45
	S/N Ratio	>48 dB
	Sync. Mode	Internal Sync
	Scanning System	2:1 Interlace
	Shutter Control	NTSC: 1/60-1/100,000 sec. PAL: 1/50-1/100,000 sec.
	BNC Video Output	Composite Video 1.0Vpp. 75 ohm
	Night Mode	Auto
White Balance	ATW	
Infrared LED	Quantity	28
	Peak Wavelength	850 nm
	Radiant Distance	20 meters
Power	Power Supply	12V DC
	Power Consumption	18 W
Lens	6 mm board lens (standard); 8 mm (option)	
Dimension	118 (L) * 78 (Ø) mm	
Weight	0.45 kg	
Ingress Protection Rating	IP66	
Operating Temperature	-10°C ~ +60°C	

สนใจ สอบถามรายละเอียดเพิ่มเติม กรุณาติดต่อ  
บริษัท เอส-วัน เทคโนโลยี จำกัด โทร. 02-991-6962 มือถือ 086-789-7434  
Email: [kitti@sone.co.th](mailto:kitti@sone.co.th)  
[www.sone.co.th](http://www.sone.co.th)